



## SPOT ON RING ROLLING PTY LTD

### ASME B16.5 CL 150 TO SUIT PIPE

AVAILABLE IN M/S, GALVANISED OR 316 STAINLESS STEEL

Nominal Size		O.D. mm	I.D. mm	P.C.D. mm	Hole Diameter	No Of Holes	Thickness mm	Approx Weight
40	1 1/2"	127	49	99	16	4	18	1.37
50	2"	152	61	121	20	4	19	2.09
80	3"	190	90	152	20	4	24	3.89
100	4"	230	115	191	20	8	24	5.37
125	5"	255	142	216	22	8	24	6.04
150	6"	280	168	241	22	8	25	7.25
200	8"	345	220	299	22	8	29	11.77
250	10"	405	275	362	26	12	30	14.95
300	12"	485	325	432	26	12	32	23.82
350	14	535	359	476	29	12	35	31.85
400	16	595	410	540	29	16	37	39.02
450	18	635	461	578	32	16	40	42.74
500	20	700	513	635	32	20	43	54.68
600	24	815	615	749	35	20	48	76.90

**ANSI 150 FLANGES CAN BE SUPPLIED IN T/D THICKNESS  
ID'S CAN BE MACHINED TO SUIT INDIVIDUAL REQUIREMENTS**