



SPOT ON RING ROLLING PTY LTD

ASME B16.5 CL150 TO SUIT POLY PIPE

AVAILABLE IN M/S, GALVANISED OR 316 STAINLESS STEEL

Nominal Size		O.D. mm	I.D. mm	P.C.D. mm	Hole Diameter	No Of Holes	Thickness mm	Approx Weight
50	1 1/2"	127	62	99	16	4	18	1.22
63	2"	152	78	121	20	4	19	1.82
90	3"	190	103	152	20	4	24	3.52
110	4"	230	128	191	20	8	24	4.91
125	5"	255	142	216	22	8	24	6.04
160	6"	280	178	241	22	8	25	6.71
200	8"	345	230	299	22	8	29	10.98
250	10"	405	290	362	26	12	30	13.37
315	12"	485	345	432	26	12	32	21.19
355	14	535	376	476	29	12	35	29.15
400	16	595	430	540	29	16	37	35.23
450	18	635	480	578	32	16	40	38.37
500	20	700	533	635	32	20	43	49.15
630	24	815	660	749	35	20	48	60.03

**ANSI 150 FLANGES CAN BE SUPPLIED IN T/D THICKNESS
ID'S CAN BE MACHINED TO SUIT INDIVIDUAL REQUIREMENTS**