



# SPOT ON RING ROLLING PTY LTD

## DIN 16 POLY

AVAILABLE IN M/S, GALVANISED OR 316 STAINLESS STEEL

Nominal Size		O.D. mm	I.D. mm	P.C.D. mm	Hole Diameter	No Of Holes	Thickness	Approx Weight
20	1/2"	95	32	65	14	4	14	0.62
25	3/4"	105	37	75	14	4	16	0.88
32	1"	115	44	85	14	4	16	1.04
40	1 1/4"	140	52	100	18	4	18	1.73
50	1 1/2"	150	62	110	18	4	18	1.93
63	2"	165	74	125	18	4	20	2.52
75	2 1/2"	185	87	145	18	8	20	2.97
90	3"	200	103	160	18	8	20	3.30
110	4"	220	125	180	18	8	22	4.09
125	5"	250	155	210	18	8	22	4.87
160	6"	285	178	240	22	8	24	6.76
200	8"	340	230	295	22	12	26	9.12
250	10"	405	290	355	26	12	28	12.40
315	12"	460	345	410	26	12	32	16.66
355	14"	520	374	470	26	16	35	25.83
400	16"	580	424	525	30	16	38	33.32
450	18"	640	478	585	30	20	42	42.24
500	20"	715	528	650	33	20	46	59.75
630	24"	840	660	770	36	20	52	78.25

**DIN 16 FLANGES CAN BE SUPPLIED IN T/D THICKNESS  
ID'S CAN BE MACHINED TO SUIT INDIVIDUAL REQUIREMENTS**