



SPOT ON RING ROLLING PTY LTD

PN16 AS4087 TO SUIT PIPE

AVAILABLE IN M/S, GALVANISED OR 316 STAINLESS STEEL

Nominal Size		O.D. Mm	I.D. Mm	P.C.D. Mm	Hole Diameter	No of Holes	Thickness MM	Approx Weight
50	2"	150	61	114	18	4	11	1.19
65	2 1/2"	165	74	127	18	4	11	1.39
80	3"	185	90	146	18	4	11	1.68
100	4"	215	115	178	18	4	13	2.54
150	6"	280	168	235	18	8	13	3.81
200	8"	335	220	292	18	8	19	7.17
225	9"	370	220	324	18	8	19	10.06
250	10"	405	275	356	22	8	19	9.90
300	12"	455	325	406	22	12	23	13.56
350	14"	525	359	470	26	12	30	25.64
375	15"	550	405	495	26	12	30	24.11
400	16"	580	410	521	26	12	30	29.63
450	18"	640	461	584	26	12	30	34.95
500	20"	705	513	641	26	16	38	52.25
550	22"	760	564	699	30	16	44	66.49
600	24"	825	615	756	30	16	48	85.23
700	28"	910	717	845	30	20	56	102.20
750	30"	995	768	927	33	20	56	130.65
800	32"	1060	819	984	36	20	56	147.40

ID'S CAN BE MACHINED TO SUIT INDIVIDUAL REQUIREMENTS