



# SPOT ON RING ROLLING PTY LTD

## PN16 AS4087 POLY SIZE

AVAILABLE IN M/S GALVANISED OR 316 STAINLESS STEEL

Nominal Size		O.D. Mm	I.D. Mm	P.C.D. Mm	Hole Diameter	No of Holes	Thickness MM	Approx Weight
63	2"	150	74	114	18	4	11	1.07
75	2 1/2"	165	87	127	18	4	11	1.25
90	3"	185	103	146	18	4	11	1.51
110	4"	215	125	178	18	4	13	2.35
160	6"	280	178	235	18	8	13	3.54
180	6" PB	280	195	235	18	8	13	3.03
200	8"	335	230	292	18	8	19	6.65
225	9"	370	240	324	18	8	19	8.99
250	10"	405	290	356	22	8	19	8.91
280	10" PB	405	300	356	22	8	19	8.22
315	12"	455	345	406	22	12	23	11.66
355	14"	525	376	470	26	12	30	23.33
375	15"	550	424	495	26	12	30	21.20
400	16"	580	424	521	26	12	30	27.47
450	18"	640	478	584	26	12	30	32.00
500	20"	705	533	641	26	16	38	47.35
560	22"	760	590	699	30	16	44	58.35
630	24"	825	660	756	30	16	48	68.25
710	28"	910	745	845	30	20	56	88.07
750	30"	995	785	927	33	20	56	121.54
800	32"	1060	840	984	36	20	56	135.37

**ID'S CAN BE MACHINED TO SUIT INDIVIDUAL REQUIREMENTS**