



SPOT ON RING ROLLING PTY LTD

TABLE D AS2129 TO SUIT PIPE

AVAILABE IN M/S, GALVANISED OR 316 STAINLESS STEEL

Nominal Size		O.D. mm	I.D. mm	P.C.D. mm	Hole Diameter	No Of Holes	Thickness mm	Approx Weight
15	1/2"	95	22	67	14	4	6	0.29
20	3/4"	100	27	73	14	4	6	0.31
25	1"	115	34	83	14	4	7	0.49
32	1 1/4"	120	43	87	14	4	8	0.58
40	1 1/2"	135	49	98	14	4	9	0.83
50	2"	150	61	114	18	4	10	1.08
65	2 1/2"	165	74	127	18	4	10	1.26
80	3"	185	90	146	18	4	11	1.68
100	4"	215	115	178	18	4	10	1.95
125	5"	255	142	210	18	8	13	3.39
150	6"	280	168	235	18	8	13	3.81
200	8"	335	220	292	18	8	13	4.91
225	9"	370	220	324	18	8	16	8.47
225	9"	370	230	324	18	8	16	8.03
250	10"	405	275	356	22	8	16	8.34
300	12"	455	325	406	22	12	19	11.20
350	14"	525	359	470	26	12	22	18.80
375	15"	550	384	495	26	12	22	19.93
400	16"	580	410	521	26	12	22	21.73
450	18"	640	461	584	26	12	25	29.13
500	20"	705	513	641	26	16	29	39.88
550	22"	760	564	699	30	16	29	43.82
600	24"	825	615	756	30	16	32	56.82
700	28"	910	717	845	30	20	35	63.88
750	30"	995	768	927	33	20	41	95.66
800	32"	1060	819	984	36	20	41	107.92
900	36"	1175	920	1092	36	24	48	148.89
1000	40"	1255	1020	1175	36	24	51	158.32
1200	48"	1490	1224	1410	36	32	60	251.72

ID'S CAN BE MACHINED TO SUIT INDIVIDUAL REQUIREMENTS