



# SPOT ON RING ROLLING PTY LTD

## TABLE D AS2129 TO SUIT POLY PIPE

AVAILABLE IN M/S, GALVANISED OR 316 STAINLESS STEEL

Nominal Size		O.D. mm	I.D. mm	P.C.D. mm	Hole Diam	No Of Holes	Thickness mm	Approx Weight
20	1/2"	95	32	67	14	4	6	0.27
25	3/4"	100	37	73	14	4	6	0.29
32	1"	115	44	83	14	4	7	0.45
40	1 1/4"	120	52	87	14	4	8	0.54
50	1 1/2"	135	62	98	14	4	9	0.75
63	2"	150	74	114	18	4	10	0.97
75	2 1/2"	165	87	127	18	4	10	1.13
90	3"	185	103	146	18	4	11	1.51
110	4"	215	125	178	18	4	10	1.81
125	5"	255	155	210	18	8	13	3.08
160	6"	280	178	235	18	8	13	3.54
180	6"	280	195	235	18	8	13	3.03
200	8"	335	230	292	18	8	13	4.55
225PB	8"	335	240	292	18	8	13	4.17
225	9"	370	240	324	18	8	16	7.57
225	9"	370	271	324	18	8	16	6.00
250	10"	405	290	356	22	8	16	7.50
280	10"	405	300	356	22	8	16	6.92
315	12"	455	345	406	22	12	19	9.63
355	14"	525	374	470	26	12	22	17.31
375	15"	550	405	495	26	12	22	17.68
375PB	15'	550	424	495	26	12	22	15.55
400	16"	580	424	521	26	12	22	20.14
450	18"	640	478	584	26	12	25	26.67
500	20"	705	528	641	26	16	29	37.09
560	22"	760	590	699	30	16	29	38.46
630	24"	825	660	756	30	16	32	45.50
710	28"	910	745	845	30	20	35	55.04
750	30"	995	785	927	33	20	41	88.98
800	32"	1060	845	984	36	20	41	96.98
900	36"	1175	940	1092	36	24	48	137.88
1000	40"	1255	1040	1175	36	24	51	145.37
1200	48"	1490	1250	1410	36	32	60	227.92

**ID'S CAN BE MACHINED TO SUIT INDIVIDUAL REQUIREMENTS**