



SPOT ON RING ROLLING PTY LTD

TABLE E AS2129 TO SUIT PIPE

AVAILABLE IN M/S, GALVANISED OR 316 STAINLESS STEEL

Nominal Size		O.D. mm	I.D. mm	P.C.D. mm	Hole Diameter	No Of Holes	Thickness mm	Approx Weight
15	1/2"	95	22	67	14	4	6	0.29
20	3/4"	100	27	73	14	4	6	0.31
25	1"	115	34	83	14	4	7	0.49
32	1 1/4"	120	43	87	14	4	8	0.58
40	1 1/2"	135	49	98	14	4	9	0.83
50	2"	150	61	114	18	4	10	1.08
65	2 1/2"	165	74	127	18	4	10	1.26
80	3"	185	90	146	18	4	11	1.68
100	4"	215	115	178	18	8	13	2.44
150	6"	280	170	235	22	8	17	4.78
200	8"	335	220	292	22	8	19	7.02
250	10"	405	275	356	22	12	22	11.20
300	12"	455	325	406	26	12	25	14.38
350	14"	525	359	470	26	12	29	24.79
400	16"	580	410	521	26	12	32	31.60
450	18"	640	461	584	26	12	35	40.78
500	20"	705	513	641	26	16	38	52.25
600	24"	825	615	756	33	16	48	84.34
700	28"	910	717	845	33	20	51	91.89
800	32"	1060	819	984	36	20	54	142.13
900	36"	1175	920	1092	36	24	64	198.52
1000	40"	1255	1020	1130	39	24	67	205.76
1200	48"	1490	1224	1410	39	32	79	327.92

**T/E FLANGES CAN BE SUPPLIED IN T/D THICKNESS
ID'S CAN BE MACHINED TO SUIT INDIVIDUAL REQUIREMENTS**