



SPOT ON RING ROLLING PTY LTD

TABLE E AS2129 FOR POLY PIPE

AVAILABLE IN M/S, GALVANISED OR 316 STAINLESS STEEL

Nominal Size		O.D. mm	I.D. mm	P.C.D. mm	Hole Diameter	No Of Holes	Thickness mm	Approx Weight
20	1/2"	95	32	67	14	4	6	0.27
25	3/4"	100	37	73	14	4	6	0.29
32	1"	115	44	83	14	4	7	0.45
40	1 1/4"	120	52	87	14	4	8	0.54
50	1 1/2"	135	62	98	14	4	9	0.75
63	2"	150	74	114	18	4	10	0.97
75	2 1/2"	165	87	127	18	4	10	1.13
90	3"	185	103	146	18	4	11	1.51
110	4"	215	125	178	18	8	13	2.24
160	6"	280	178	235	22	8	17	4.49
180	6"	280	195	235	22	8	17	3.83
200	8"	335	230	292	22	8	19	6.50
225	8"	335	240	292	22	8	19	5.95
250	10"	405	290	356	22	12	22	10.05
280	10"	405	300	356	22	12	22	9.25
315	12"	455	345	406	26	12	25	12.31
355	14"	525	374	470	26	12	29	22.82
400	16"	580	424	521	26	12	32	29.30
450	18"	640	478	584	26	16	35	36.75
500	20"	705	528	641	26	16	38	48.60
630	24"	825	660	756	33	16	48	67.36
710	28"	910	745	845	33	20	51	79.02
800	32"	1060	845	984	36	20	54	127.73
900	36"	1175	940	1092	36	24	64	183.85
1000	40"	1255	1040	1130	39	24	67	188.75
1200	48"	1490	1250	1410	39	32	79	296.59

**TABLE E FLANGES CAN BE SUPPLIED IN T/D THICKNESS.
ID'S CAN BE MACHINED TO SUIT INDIVIDUAL REQUIREMENTS**